

iBOXPC-4000A



Features:

- Industrial Fanless design small size system with Gemini Lake CPU
- Intel Entry Level N4000 Dual Core CPU
- Dual Display 1x VGA, 1x HDMI (support 4K)
- 4x USB 3.0 Type A and 1x COM
- One 2.5" HDD/SSD space
- Support eMMC 32/64G(Optional)
- Support WiFi/Bluetooth function(Optional)
- High performance/low price ratio for Digital Signage, and Retail / Hospitality application

Specification:

Model Name	iBOXPC 4000A	
Main Board	Processor	Intel® Gemini Lake Processor N4000 DC 6W 1.1GHz (Fanless)
	Chipset	CPU integrated
	System Memory	1 x 1.2V DDR4 SO-DIMM slot , Max. to 8GB, support up to 2400MHz
	Graphic Engine	Intel® UHD Graphics 600
Storage HDD/SSD	HDD/SSD	1 x 2.5" SATA drive for HDD/SSD
	Flash memory	1 x NAND FL EMMC 32GB/64GB (Option)
Extension	M.2 slot	1 x M.2 slot(Support NGFF-2230 Wifi/BT) (Option)
I/O	USB	2 x USB 3.0 Front, 2 x USB 3.0 Rear
	Serial/COM	1 COM
	VGA	1 x VGA, 1 x HDMI 1.4b Rear
	LAN port	1 x RJ45 LAN port Rear
	Cash Drawer Port	Nil
	DC Jack	1 x DC IN side
	LPT Port	Nil
	PS2	Nil
	Audio out/Mic In	1 x Microphone Jack & 1 x HeadphoneJack Front
	Power LED	Yes
	WiFi	1 x M.2 slot(Support NGFF-2230 Wifi/BT) with 2 pcs Antenna (Option)
	Power Switch	1 Front
	Power Adapter	DC 19 volt 40W power adapter
Compliance	EMC Safety	CE, FCC, LVD, RoHS
	Ventilation	Fanless
Environment	Operating Temperature	0 °C ~ 50°C (32°F ~ 122°F)
	Storage Temperature	-10°C ~ 60°C (-4°F ~ 140°F)
	Operating Humidity	20% - 85% RH non condensing
	Storage Humidity	20% - 85% RH non condensing
Dimension (WxHxD)	54.4 x 109.4 x 131mm	
Weight	0.8Kg (1.2KG with adapter)	
Mounting	Supports 75 x 75 and 100 x 100 mm and wall mount kit (Option)	
OS support	Window10 IOT	
Packing	Box Packing Capacity: 6 pcs	
	Carton Size: 411x403x282 mm	

Dimension:

